

PRO_AUDIO_WAV_LOW_SPEC_SHEET.indd 1 25/07/2022 13:21

WAV-LOW

Dual 15 inch high-power upper bass box



FEATURES

- Low to mid frequency enclosure
- Rear-loaded transmission line design
- 2 x high-powered 15 inch drivers
- Reproduces low, tight and responsive bass

SPECIFICATION

Enclosure Type Back-loaded horn, low-mid box

Frequency Response 50 Hz to 2 kHz
Sensitivity (1w/1m) 103 dB

Nominal Impedance 2 x 8 Ω

Power Handling 1200 W RMS, 2400 W program

Maximum SPL 134 dB cont., 140 dB peak

 Driver Configuration
 2 × 15 inch (381 mm) ferrite LF drivers

 Connectors
 1 × Neutrik SpeakON™ NL4MPR


 Dimensions (WxDxH)
 1529 × 905 × 793 mm (60.2 × 35.6 × 31.2 inch)


Weight 179 kg (394.7 lb)

Enclosure 18 mm (0.7 inch) birch plywood

Finish Impact-resistant, black textured polyurethane







GS-WAVE SERIES

PRO_AUDIO_WAV_LOW_SPEC_SHEET.indd 2 25/07/2022 13:21